

Vanguard V400 14HP Electric Start TAPER Shaft Engine (GENSPEC)

Prod Code: 3000-BRIG1-21989

GENERATOR SPEC ENGINE

- **EASIER STARTING** with new optimised starting design
- **LOWER MAINTENANCE** with cyclonic air filter (up to 600 hour replacement interval) and advanced oil management system, increasing oil life by up to 50% (up to 200 hour replacement interval)
- **ENHANCED PROTECTION** with Vanguard's 'TransportGuard' eliminates oil/fuel dilution problem and offers 3-in-1 control lever
- **USER COMFORT** with Lower noise and Less vibration
- **UP TO 4 YEAR WARRANTY** with 3 year standard warranty and additional 1 year warranty for registering your engine with Vanguard warranty online
https://www.vanguardpower.com/eu/en_gb/support/engine-registration.html

All with a lower total cost of ownership than the competition.

The new Vanguard 400 is built from the ground up to deliver what your customers need to get the job done. It outperforms the rest with exclusive market-driven innovations like TransportGuard™ – a 3-in-1 control that eliminates oil/fuel dilution. Plus it's a drop-fit replacement, no re-engineering required. Upgrade to the Vanguard 400 – the OHV engine that drives demand for your brand.

SPECIFICATIONS

| | |
|----------------------------|--|
| Engine Type | Single cylinder 4-stroke air-cooled OHV (Overhead Valve) |
| Recoil Start | Yes |
| Electric Start (Key Start) | Yes |
| Charge Coil Output | 20A |
| Model Number | 25V3 |
| Gross kW* @ 3'600 rpm | 10.4 |
| Gross HP* @ 3'600 rpm | 14.0 |
| Displacement (cc) | 408 |
| Cylinder | Cast Iron Sleeve |
| Bore (mm) | 88.0 |
| Stroke | (mm) 67.0 |
| Fuel Tank Capacity (l) 6.1 | |
| Oil Capacity (l) | 0.94 |
| Compression Ratio | 8.3:1 |
| Air Cleaner | Integrated Cyclonic Air Cleaner |
| Ignition System | CDI Ignition |
| Lubrication System | Splash Lubrication |
| Length (mm) | 359 |
| Width (mm) | 444 |
| Height (mm) | 459 |
| Dry Weight (kg) | 35.5 |
| Commercial Warranty | 3 + 1 Year Limited |

