## Honda GX690 TXF9 1 1/8 **Inch Keyway Shaft Engine**

Prod Code: 3000-HOND-20497

 $11/8^{\prime\prime}$  (28.575mm) Keyway Shaft Oil Alert Petrol Engine. Equipped with key operated electric start.

NO CONTROL BOX ON SIDE OF ENGINE

On this specification of engine both the throttle control and the choke control are setup for remote operation and NOT with a throttle lever, as in the engine image.

The GX690 engine is suitable for construction equipment, generators and other professional heavy-duty applications.

## Engine features:

•The OHV design enhances combustion efficiency
•Variable ignition timing (digital CDI) results in high power output, reduced fuel consumption and excellent exhaust emission performance
•The high-efficiency cooling fan generates higher airflow with reduced noise levels
•High quality materials and purpose-built components ensure reliable, long-term use
•Meets world's most stringent environmental legislation
•Low fuel and oil consumption

SPECIFICATIONS	
Engine type	Air cooled 4-stroke OHV petrol engine 90° V-twin design horizontal shaft
Shaft Diameter	11/8 Inch Keyway Shaft
Bore x stroke	2 / 78 x 72 mm
Displacement	688 cm3
Compression ratio	9.3 : 1
Net power	16.5 kW (22.1 HP) / 3 600 rpm
Cont. rated power 3 000 rpm	11.5 kW (15.4 HP)
Cont. rated power 3 600 rpm	13.0 kW (17.4 HP)
Max. net torque	48.3 Nm / 4.93 kgfm / 2 500 rpm
Ignition system	Digital CDI with variable ignition timing
Carburetor	2-barrel carburetor fuel cut solenoid
Lubrication	Full-pressure
Starting system	Electric starter
Charge Coil	17A
Choke Type	Remote (No Lever)
Throttle Type	Remote (No Lever)
Control Box	Included
Fuel cons. at cont rated power	6.7 L/hr - 3 600 rpm
Engine oil capacity	1.9
Dimensions (L x W x H)	429 x 410 x 438 mm
Dry weight	44.4 kg





