

# LPG Dual Fuel Honda EU22i Door Mounted 2.2kw Generator

Prod Code: 5000-HOND2-19002

- FREE GENUINE HONDA 600ML BOTTLE OF OIL. WORTH £6.00

The new super silent Honda EU22i replaces the Honda EU20i. LPG propane gas / Petrol Dual fuel Unit. Up to 50% reduction in fuel costs and CO2 emissions when operating on LPG. Fully detachable door mounted LPG conversion kit with thumbscrew removable fitting.

Compact, quiet, lightweight and reliable. The Honda EU range has the ability to power even the most sensitive electronic equipment by means of inverter controlled output.

The Honda EU22i delivers 2200 watts of portable, clean and low noise power. Its super quiet operation, means it is the perfect leisure generator, whilst also being suited to professional applications. This compact unit is powerful enough for all kinds of tasks, whether you are abroad in a motorhome or caravan, in need of a emergency back up when theres a power cut, or a market trader in need of continuous super silent power supply.

The enclosed suitcase type casing keeps noise down to just 52 decibels. And the unique Ecothrottle means the engine only runs as fast as the load demands, ensuring maximum fuel efficiency and noise reduction. Hondas engine auto-decompression makes the pull start amongst the easiest of all generators and rubber feet take out any buzzing vibration to the floor.

\*BBQ connecter available with this kit - Bullfinch type.

## SPECIFICATIONS

|   |                                |
|---|--------------------------------|
| Output technology                           | Inverter                       |
| Type  | Single phase                   |
| Maximum output (W)                          | 2200                           |
| Rated output (W)                            | 1800                           |
| Rated voltage (V)                           | 230                            |
| Rated frequency (Hz)                        | 50                             |
| Rated current (A)                           | 7.8                            |
| DC rated output                             | 12V / 8A                       |
| Engine model                                | GXR120                         |
| Engine type                                 | 4-stroke OHV 1 cylinder        |
| Displacement (cm <sup>3</sup> )             | 121                            |
| Bore stroke (mm)                            | 56 x 40                        |
| Engine speed (rpm)                          | 5000 max                       |
| Cooling system                              | Forced air                     |
| Ignition system                             | Transistor                     |
| Oil capacity (L)                            | 0.4                            |
| Fuel tank capacity (L)                      | 3.6                            |
| Operating time at rated                     | 3h30                           |
| Starter system                              | Recoil                         |
| Noise Level (1/4 load) (dB(a)@7M)           | 52                             |
| Sound pressure level at workstation (dB(A)) | 71                             |
| Guaranteed sound power level (dB(A))        | 89                             |
| Fuel type                                   | Unleaded petrol or LPG Propane |
| Petrol Usage at 75%(L/H)                    | 0.93                           |
| LPG propane Usage at 75% (Kg/H)             | 0.4                            |

