

2 x Honda EU22i LPG Propane Dual Fuel 4.4kw Linked Silent Inverter Generators

Prod Code: 5000-HOND2-19036

- 2 x FREE HOURS METERS - FITTED. WORTH £29.50 EACH
- 2 x FREE GENUINE HONDA 600ML BOTTLES OF OIL. WORTH £6.00 EACH

The quietest and most portable 4.4kW power supply on the market. Dual generator LPG gas / Petrol Dual fuel Unit. Up to 50% reduction in fuel costs and CO2 emissions when operating on LPG

This assembly offers the user the ability to operate two generators simultaneously from one LPG bottle. During operation of two generators, if then only one generator is required, simply disconnect the quick release coupling from one of the units. This will stop that generator and the other will continue to run. When both are required again, simply reconnect the quick release coupling and start the generator in the normal way.

Compact, quiet, lightweight and reliable. The Honda EU range has the ability to power even the most sensitive electronic equipment by means of inverter controlled output.

The Honda EU22i delivers 2200 watts of portable, clean and low noise power. It's super quiet operation, means it is the perfect leisure generator, whilst also being suited to professional applications. This compact unit is powerful enough for all kinds of tasks, whether you are abroad in a motorhome or caravan, in need of a emergency back up when theres a power cut, or a market trader in need of continuous super silent power supply.

The enclosed suitcase type casing keeps noise down to just 52 decibels. And the unique Ecothrottle means the engine only runs as fast as the load demands, ensuring maximum fuel efficiency and noise reduction. Honda's engine auto-decompression makes the pull start amongst the easiest of all generators and rubber feet take out any buzzing vibration to the floor.

- * also available in petrol only version
- * also available without parallel cable to power two separate 2.2kW loads
- * Other LPG options are available with these generators

SPECIFICATIONS

Type	Portable
Max output (W)	4400
Voltage stability (%)	+ or - 1
Output voltage (V)	230
Rated output (W)	3600
Frequency rating (Hz)	50
DC voltage (volts)	12
Power Stability	Inverter Technology®
DC current per unit (amps)	8
Engine type	GX100
Type	single cylinder 4-stroke OHV air cooled
Oil capacity per unit	0.4 litre with Oil Alert®
Starter system	Recoil
Length per unit (mm)	510
Width per unit (mm)	290
Height per unit (mm)	425
Dry weight per unit (kg)	21
Noise Level (1/4 load) (dB(a))	52
Petrol Run Time up to (hrs)	10
Fuel tank capacity per unit (litres)	3.6
Petrol Usage at 75% per unit (L/H)	0.93
LPG Usage at 75% per unit (Kg/H)	0.5

