

Baumax VP16/44 46cm Plate Compactor

Prod Code: 6000-BAUM2-1916

The VP16/44 has the excitor unit located closer to the center of the machine. This decreases the overall length for a more compact design and allows a tubular steel protective frame to be fitted around the plate compactor.

Equipped with a PU Mat & Transport Wheels as standard. It is suitable for professional compaction of the subsoil and shaking in of block paving walkways, garden paths and areas of low to medium traffic load.

Features / characteristics

- Loncin commercial engine
- incl. polyurethane mat and transport axis
- folding guide handle (firmly locked!)
- very good climb performance
- excellent starting performance, even at low temperatures
- stable steel frame with a hook
- automatic shutdown in case of low engine oil level

SPECIFICATIONS

Model	VP16/44
Engine	Loncin 196cc
Engine Type	Petrol Single cylinder OHV 4-stroke air-cooled
Start system	recoil
Weight	102 kg
Compaction force (pressure)	20 kN (2040kg)
Compaction depth max.	30 cm (depending on soil conditions)
Propulsion max.	25 m / min (depending on soil conditions)
Gradeability max.	30% (depending on soil conditions)
Plate size (L x B)	550 mm x 460 mm
Dimensions L x W x H	1030 x 460mm x 960mm

