

# Atlas Copco LP9-20P 20 L/Min Hydraulic Pack + LS14 Cut off Saw

Prod Code: 6040-ATLA-21986

You can use the Atlas Copco power packs virtually anywhere: fitted with wheels and handles, they are easy to manoeuvre around building sites. They are easy to start, the noise level is low, and when they are not in use, the power packs are small enough to be stored on shelves. They are also lightweight enough that two people can lift one up and fit it in the back of a van.

This power pack is equipped with Power On Demand (POD). This hydraulic regulatory system automatically idles the engine when the tool is not being used and speeds it up when the tool is activated.

## CUT OFF SAW

These powerful, light and compact saws can be used to cut through concrete, asphalt and steel. Their simple hydraulic design with direct drive reduces maintenance, especially in comparison with belt-driven saws. They are easy to use thanks to the open cutting face, even under the most demanding conditions. With a lightweight cart you can use the saws for floor, road and other light surface jobs.

## Features & benefits

Simple design with direct drive motor  
Open visible cutting face  
High power-to-weight ratio  
Compact and slim design

## Applications

Cuts 133-160 mm (5 in) depth  
Works in dust, slurry and underwater

## Used for cutting

Concrete, reinforced concrete  
Asphalt  
Steel

## Used with

Dry and wet diamond discs  
Abrasive steel cutting discs



## SPECIFICATIONS

Honda	GX270
HP	9
Oil flow	20 l per min
Weight (incl oil)	80 kg
Length	630 mm
Width	530 mm
Height	640 mm
Max pressure	150 bar
Fuel capacity	6 l
Hose included	YES
Power on Demand (POD)	YES
Oil control: engine oil	YES
Electric start	NO
Sound power level guaranteed Lw (2000/14/EC)*	101 dB(A)
Sound pressure level (ISO 11203)* Lp r 1m	87 dB(A)
EHTMA class	C
Saw weight incl. hoses	12 kg
Service weight incl disc	13.5 kg
Oil flow	20 - 30 l/min
Max pressure	170 bar
Revolutions	2500 - 4000 rpm
Speed	46 - 75 m/s
Disc size	355 mm
Arbor size	25,4 mm

Cutting depth	133 mm
Vibration level 3 axes (ISO 28927-8) 20 lpm*	4.9 m/s
Sound power level guaranteed Lw (2000/14/EC)*	99 dB(A)
Sound pressure level (ISO 11203)* Lp r-1m	86 dB(A)
EHTMA class	C/D