

Husqvarna K4000 Wet and Dry 110v Disc Cutter Saw

Prod Code: 6050-HUSQ-20642

REPLACES HUSQVARNA K3000. INCLUDES FREE TACICUT S50 BLADE.

With the new K 4000 series of cutters Husqvarna has performed an upgrade on the much appreciated K 3000 series, adding a number of beneficial functions that will facilitate service as well as increase performance. However, the efficiency remains the same with user-friendly ergonomics and forward-rotating blades for minimum effort.

This electric all-round cutter minimises the amount of water and slurry. Unlike other electric cutters, the blade rotates forward, cutting into the material efficiently with minimum effort on the operator. K 4000 is easily adaptable for dry cutting with the Vac attachment accessory for minimal dust generation.

Constant-flow water valve
When wet cutting, water volume is regulated for a consistent flow to the blade. It uses just enough water to bind the dust and create a slurry, so you're not wasting water.

Ergonomically designed rear handle
Hassle-free operation is achievable thanks to the convenient location of the power cable, so it does not interfere with the trigger button. Small incremental improvements to the layout can really improve the user experience, so that you can complete the task with maximum comfort.

Easy serviceability
Servicing and assembly are further simplified since the previous K3000 model, with Torx screws and a one-piece inspection lid. Carbon rotor brushes help to increase service intervals so you can spend more time cutting and less time waiting.

Simple blade change
A large outlet in the blade guard and a spindle with quick-acting locks makes blade replacement even easier than previous models

Overload protection
With the Elgard™ system, the rotation speed is dynamically varied in order to protect against overload.

Electronic Softstart™
Normal, slow-acting fuses are no problem for the K 4000

High durability and low noise levels
This electric power cutter had a high level of durability, with low noise levels and minimised loss of power.



SPECIFICATIONS

Voltage	110v
Power Consumption	2.2kW
Rated input power	2.7kW
Max Cutting depth	125mm
Max Blade Diameter	350mm
Arbor diameter	25.4mm
Max blade thickness	5.6mm
handle vibration	3.5 M/S2
Length	631mm
Width	221mm
Height	313mm
Weight	7.6Kg