Briggs & Stratton 14HP Elec Start XR2100 6 to 1 Reduction Engine

Prod Code: 3000-BRIG1-19009

1" (25.4mm) 6:1 Reduction Keyway Shaft Oil Alert Petrol Engine. Equipped with key operated electric start. Briggs & Stratton engine fitted with USA manufactured Noram 6:1 Gearbox

Suitable for applications where high torque and low RPM are required. Gearbox can be fitted with output shaft in right position (pictured) or in left position, to suit application.

Briggs & Stratton general purpose horizontal shaft engines are built to be tough, reliable and efficient. Feature for feature, they offer you the best value available. The 2100 SERIES™ engine is ideal for tillers, pressure washers, and water pumps.

Lo-Tone™ Muffler - Delivers low noise and good tonal quality

Dual Ball Bearings - Provides added durability and extends engine life

Cartridge Air Cleaner with foam pre-cleaner (dual element) - Provides improved protection against airborne debris entering the engine

Magnetron® Electronic Ignition System - Ensures maintenance free easy starting Cast Iron Sleeve - Adds integrity and durability that withstand wear and abuse while providing improved oil control

Mechanical Governor - Controls the engine speed to deliver more usable power under heavy usage

 $\ensuremath{\mathsf{OHV}}$ Technology - Optimized performance that delivers longer engine life and improved fuel economy

Engine Type Single cylinder OHV 4-stroke air-cooled Model Number 25T2 Gross Torque (Nm) @ 2'600 rpm 28.5* Displacement (cc) 420 Cylinder Cast Iron Sleeve Bore (mm) 90.0 Stroke (mm) 66.0 Fuel Tank Capacity (l) 6.6 Oil Capacity (l) 1.1 Dry Weight (kg) 48 Dimensions Length (mm) 505	
Gross Torque (Nm) @ 2'600 rpm 28.5* Displacement (cc) 420 Cylinder Cast Iron Sleeve Bore (mm) 90.0 Stroke (mm) 66.0 Fuel Tank Capacity (I) 6.6 Oil Capacity (I) 1.1 Dry Weight (kg) 48	
Displacement (cc) 420 Cylinder Cast Iron Sleeve Bore (mm) 90.0 Stroke (mm) 66.0 Fuel Tank Capacity (l) 6.6 Oil Capacity (l) 1.1 Dry Weight (kg) 48	
Cylinder Cast Iron Sleeve Bore (mm) 90.0 Stroke (mm) 66.0 Fuel Tank Capacity (I) 6.6 Oil Capacity (I) 1.1 Dry Weight (kg) 48	
Bore (mm) 90.0 Stroke (mm) 66.0 Fuel Tank Capacity (I) 6.6 Oil Capacity (I) 1.1 Dry Weight (kg) 48	
Stroke (mm) 66.0 Fuel Tank Capacity (I) 6.6 Oil Capacity (I) 1.1 Dry Weight (kg) 48	
Fuel Tank Capacity (I) 6.6 Oil Capacity (I) 1.1 Dry Weight (kg) 48	
Oil Capacity (I) Dry Weight (kg) 1.1 48	
Dry Weight (kg) 48	
7 7 3 7 3 7	
Dimensions Length (mm) 505	
Dimensions Width (mm) 450	
Dimensions Height (mm) 457	
Recoil Start Yes	
Electric Start Yes	

