

# Briggs & Stratton 14HP Elec Start XR2100 Tapered Shaft Engine

**Prod Code: 3000-BRIG2-299**

7/8" Tapered Shaft (Generator Spec) Oil Alert Petrol Engine. Equipped with key operated electric start

Briggs & Stratton general purpose horizontal shaft engines are built to be tough, reliable and efficient. Feature for feature, they offer you the best value available. The 2100 SERIES™ engine is ideal for tillers, pressure washers, and water pumps.

Lo-Tone™ Muffler - Delivers low noise and good tonal quality

Dual Ball Bearings - Provides added durability and extends engine life

Cartridge Air Cleaner with foam pre-cleaner (dual element) - Provides improved protection against airborne debris entering the engine

Magnetron® Electronic Ignition System - Ensures maintenance free easy starting

Cast Iron Sleeve - Adds integrity and durability that withstand wear and abuse while providing improved oil control

Mechanical Governor - Controls the engine speed to deliver more usable power under heavy usage

OHV Technology - Optimized performance that delivers longer engine life and improved fuel economy

## SPECIFICATIONS

|                               |   |
|-------------------------------|---|
| Engine Type                   | Single cylinder OHV 4-stroke air-cooled |
| Model Number                  | 25T2                                    |
| Gross Torque (Nm) @ 2'600 rpm | 28.5*                                   |
| Displacement (cc)             | 420                                     |
| Cylinder                      | Cast Iron Sleeve                        |
| Bore (mm)                     | 90.0                                    |
| Stroke (mm)                   | 66.0                                    |
| Fuel Tank Capacity (l)        | 6.6                                     |
| Oil Capacity (l)              | 1.1                                     |
| Dry Weight (kg)               | 31.0                                    |
| Dimensions Length (mm)        | 405                                     |
| Dimensions Width (mm)         | 450                                     |
| Dimensions Height (mm)        | 457                                     |
| Recoil Start                  | Yes                                     |
| Electric Start                | Yes                                     |



## V-TYPE

