Honda GX630 QXF 1 Inch **Keyway Shaft V-Twin Engine**

Prod Code: 3000-HOND-20060

1" (25.4mm) Diameter Shaft Oil Alert Petrol Engine. Equipped with key operated electric start. This specification of engine has a lever to control the choke at the engine control box, as pictured. The throttle control is setup for remote operation and NOT with a throttle lever, as in the main engine image. THIS CAN BE PURCHASED AS A SEPERATE PART AND FITTED BY US (P/N. HOND-MISC-22345)

The GX630 engine is suitable for construction equipment, generators and other professional heavy-duty applications.

Engine features:

- The OHV design enhances combustion efficiency
 Variable ignition timing (digital CDI) results in high power output, reduced fuel consumption and excellent exhaust emission performance
 The high-efficiency cooling fan generates higher airflow with reduced noise levels
 High quality materials and purpose-built components ensure reliable, long-term use
 Meets world's most stringent environmental legislation
 Low field and oil consumption

ı	rieets	WOIIG	5 111051	SUIII	gent t
١	Low fi	iel and	l oil cor	nsiim	ntion

SPECIFICATIONS	SPECIFICATIONS			
Engine type	Air cooled 4-stroke OHV petrol engine 90° V-twin design horizontal shaft			
Shaft Diameter	1 Inch Keyway Shaft			
Bore x stroke	2 / 78 x 72 mm			
Displacement	688 cm3			
Compression ratio	9.3 : 1			
Net power	15.5 kW (20.8 HP) / 3 600 rpm			
Cont. rated power 3 000 rpm	10.5 kW (14.1 HP)			
Cont. rated power 3 600 rpm	12.0 kW (16.1 HP)			
Max. net torque	48.3 Nm / 4.93 kgfm / 2 500 rpm			
Ignition system	Digital CDI with variable ignition timing			
Carburetor	2-barrel carburetor fuel cut solenoid			
Lubrication	Full-pressure			
Starting system	Electric starter			
Charge Coil	17A			
Choke Type	Lever			
Throttle Type	Remote			
Control Box	Included			
Fuel cons. at cont rated power	6.0 L/hr - 3 600 rpm			
Engine oil capacity	1.9			
Dimensions (L x W x H)	405 x 410 x 438 mm			
Dry weight	44.4 kg			
Recoil Start	No			
Electric Start	Yes			





