

Honda GX390 LKE Electric Start 2:1 Reduction Engine

Prod Code: 3000-HOND-25282

2:1 Reduction Box Oil Alert Petrol Engine. Equipped with key operated electric start The GX390 engine is suitable for a wide range of heavy-duty applications such as construction equipment, tillers, generators, welders, pumps and other industrial applications.


Engine features:


- Engine reatures.
 The OHV design enhances combustion efficiency
 A variable ignition timing (digital CDI) results in high power output, reduced fuel consumption and excellent exhaust emissions performance.
 Easy starting with an automatic decompression system and an easy-to-grip soft recoil starter handle
 High quality materials and purpose-built components ensure reliable long-term use
 Meets world's most stringent environmental legislation
 Guaranteed low fuel and oil consumption
 Reduced vibration and noise level

SPECIFICATIONS

SPECIFICATIONS	
Engine Type	Single cylinder OHV 4-stroke air-cooled
Max. Net Torque (Nm) @ 2'500 rpm	26.5
Displacement (cc)	389
Cylinder	Cast Iron Sleeve
Bore (mm)	88.0
Stroke (mm)	64.0
Fuel Tank Capacity (I)	6.1
Oil Capacity (I)	1.1
Dry Weight (kg)	31.7
Dimensions Length (mm)	406
Dimensions Width (mm)	460
Dimensions Height (mm)	448
Recoil Start	Yes
Electric Start	Yes







L-TYPE



GearGB Hart Industrial Tools White Hart Court, Hart Village, Hartlepool TS27 3AW