## Honda EU10i 1kw Quiet Inverter Petrol Generator

Prod Code: 5000-HOND1-76

• FREE GENUINE HONDA 600ML BOTTLE OF OIL. WORTH £6.00

Compact, quiet, lightweight and reliable. The Honda EU range has the ability to power even the most sensitive electronic equipment by means of inverter controlled output.

The Honda EU10i delivers 1000 watts of portable, clean and low noise power. It's super quiet operation, means it is the perfect leisure generator, whilst also being suited to proffesional applications. This compact unit is powerful enough for all kinds of tasks, whether you are abroad in a motorhome or caravan, in need of a emergency back up when theres a power cut, or a market trader in need of continuous super quiet power supply.

The enclosed suitcase type casing keeps noise down to just 52 decibels. And the unique Ecothrottle means the engine only runs as fast as the load demands, ensuring maximum fuel efficiency and noise reduction. Honda's engine auto-decompression makes the pull start amongst the easiest of all generators and rubber feet take out any buzzing vibration to the floor.

Primary usage Leisure Use Type Portable  Max output (W) 1.000  Voltage stability (%) + or - 1  Output voltage (V) 230  Rated output (W) 900  Frequency rating (Hz) 50  DC voltage (volts) 12  Power Stability Inverter Technology®  DC current (amps) 8  Engine type GXH50  Type single cylinder 4-stroke OHV air cooled  Oil capacity 0.25 litre with Oil Alert®  Starter system Recoil  Length (mm) 450  Width (mm) 240  Height (mm) 380  Dry weight (kg) 13  Noise Level (I/4 load) (dB(a)) 52  Run Time up to (hrs) 8  Fuel tank capacity (litres) 2.30  Fuel type Unleaded petrol		
Type Portable  Max output (W) 1.000  Voltage stability (%) + or - 1  Output voltage (V) 230  Rated output (W) 900  Frequency rating (Hz) 50  DC voltage (volts) 12  Power Stability Inverter Technology®  DC current (amps) 8  Engine type GXH50  Type GXH50  Type single cylinder 4-stroke OHV air cooled  Oil capacity 0.25 litre with Oil Alert®  Starter system Recoil  Length (mm) 450  Width (mm) 240  Height (mm) 380  Dry weight (kg) 13  Noise Level (1/4 load) (dB(a)) 52  Run Time up to (hrs) 8  Fuel tank capacity (litres) 2.30	SPECIFICATIONS	
Max output (W)  Voltage stability (%)  Poutput voltage (V)  Rated output (W)  Prequency rating (Hz)  DC voltage (volts)  Power Stability  Inverter Technology®  Current (amps)  Engine type  GXH50  Type  Single cylinder 4-stroke OHV air cooled  Oil capacity  O.25 litre with Oil Alert®  Starter system  Recoil  Length (mm)  450  Width (mm)  Height (mm)  380  Dry weight (kg)  Run Time up to (hrs)  8  1.000  230  1.000  230  230  8  Fuel tank capacity (litres)  1.000  230  230  230  230  230  230  230	Primary usage	Leisure Use
Voltage stability (%) + or - 1  Output voltage (V) 230  Rated output (W) 900  Frequency rating (Hz) 50  DC voltage (volts) 12  Power Stability Inverter Technology®  DC current (amps) 8  Engine type GXH50  Type single cylinder 4-stroke OHV air cooled  Oil capacity 0.25 litre with Oil Alert®  Starter system Recoil  Length (mm) 450  Width (mm) 240  Height (mm) 380  Dry weight (kg) 13  Noise Level (1/4 load) (dB(a)) 52  Run Time up to (hrs) 8  Fuel tank capacity (litres) 2.30	Type	Portable
Output voltage (V ) 230  Rated output (W) 900  Frequency rating (Hz) 50  DC voltage (volts) 12  Power Stability Inverter Technology®  DC current (amps) 8  Engine type GXH50  Type single cylinder 4-stroke OHV air cooled  Oil capacity 0.25 litre with Oil Alert®  Starter system Recoil  Length (mm) 450  Width (mm) 240  Height (mm) 380  Dry weight (kg) 13  Noise Level (1/4 load) (dB(a)) 52  Run Time up to (hrs) 8  Fuel tank capacity (litres) 2.30	Max output (W)	1.000
Rated output (W) 900  Frequency rating (Hz) 50  DC voltage (volts) 12  Power Stability Inverter Technology®  DC current (amps) 8  Engine type GXH50  Type single cylinder 4-stroke OHV air cooled  Oil capacity 0.25 litre with Oil Alert®  Starter system Recoil  Length (mm) 450  Width (mm) 240  Height (mm) 380  Dry weight (kg) 13  Noise Level (1/4 load) (dB(a)) 52  Run Time up to (hrs) 8  Fuel tank capacity (litres) 2.30	Voltage stability (%)	+ or - 1
Frequency rating (Hz) 50  DC voltage (volts) 12  Power Stability Inverter Technology®  DC current (amps) 8  Engine type GXH50  Type single cylinder 4-stroke OHV air cooled  Oil capacity 0.25 litre with Oil Alert®  Starter system Recoil  Length (mm) 450  Width (mm) 240  Height (mm) 380  Dry weight (kg) 13  Noise Level (1/4 load) (dB(a)) 52  Run Time up to (hrs) 8  Fuel tank capacity (litres) 2.30	Output voltage (V )	230
DC voltage (volts)  Power Stability  Inverter Technology®  DC current (amps)  8  Engine type  GXH50  Type  Single cylinder 4-stroke OHV air cooled  Oil capacity  O.25 litre with Oil Alert®  Starter system  Recoil  Length (mm)  450  Width (mm)  240  Height (mm)  380  Dry weight (kg)  13  Noise Level (1/4 load) (dB(a))  52  Run Time up to (hrs)  8  Fuel tank capacity (litres)  230	Rated output (W)	900
Power Stability Inverter Technology®  DC current (amps) 8  Engine type GXH50  Type single cylinder 4-stroke OHV air cooled  Oil capacity 0.25 litre with Oil Alert®  Starter system Recoil  Length (mm) 450  Width (mm) 240  Height (mm) 380  Dry weight (kg) 13  Noise Level (1/4 load) (dB(a)) 52  Run Time up to (hrs) 8  Fuel tank capacity (litres) 2.30	Frequency rating (Hz)	50
DC current (amps) 8 Engine type GXH50 Type single cylinder 4-stroke OHV air cooled Oil capacity 0.25 litre with Oil Alert® Starter system Recoil Length (mm) 450 Width (mm) 240 Height (mm) 380 Dry weight (kg) 13 Noise Level (1/4 load) (dB(a)) 52 Run Time up to (hrs) 8 Fuel tank capacity (litres) 2.30	DC voltage (volts)	12
Engine type GXH50  Type single cylinder 4-stroke OHV air cooled  Oil capacity O.25 litre with Oil Alert®  Starter system Recoil  Length (mm) 450  Width (mm) 240  Height (mm) 380  Dry weight (kg) 13  Noise Level (1/4 load) (dB(a)) 52  Run Time up to (hrs) 8  Fuel tank capacity (litres) 2.30	Power Stability	Inverter Technology®
Type         single cylinder 4-stroke OHV air cooled           Oil capacity         0.25 litre with Oil Alert®           Starter system         Recoil           Length (mm)         450           Width (mm)         240           Height (mm)         380           Dry weight (kg)         13           Noise Level (1/4 load) (dB(a))         52           Run Time up to (hrs)         8           Fuel tank capacity (litres)         2.30	DC current (amps)	8
Oil capacity	Engine type	GXH50
Starter system       Recoil         Length (mm)       450         Width (mm)       240         Height (mm)       380         Dry weight (kg)       13         Noise Level (1/4 load) (dB(a))       52         Run Time up to (hrs)       8         Fuel tank capacity (litres)       2.30	Type	single cylinder 4-stroke OHV air cooled
Length (mm)       450         Width (mm)       240         Height (mm)       380         Dry weight (kg)       13         Noise Level (1/4 load) (dB(a))       52         Run Time up to (hrs)       8         Fuel tank capacity (litres)       2.30	Oil capacity	0.25 litre with Oil Alert®
Width (mm)       240         Height (mm)       380         Dry weight (kg)       13         Noise Level (1/4 load) (dB(a))       52         Run Time up to (hrs)       8         Fuel tank capacity (litres)       2.30	Starter system	Recoil
Height (mm) 380  Dry weight (kg) 13  Noise Level (1/4 load) (dB(a)) 52  Run Time up to (hrs) 8  Fuel tank capacity (litres) 2.30	Length (mm)	450
Dry weight (kg) 13 Noise Level (1/4 load) (dB(a)) 52 Run Time up to (hrs) 8 Fuel tank capacity (litres) 2.30	Width (mm)	240
Noise Level (1/4 load) (dB(a)) 52 Run Time up to (hrs) 8 Fuel tank capacity (litres) 2.30	Height (mm)	380
Run Time up to (hrs) 8 Fuel tank capacity (litres) 2.30	Dry weight (kg)	13
Fuel tank capacity (litres) 2.30	Noise Level (1/4 load) (dB(a))	52
	Run Time up to (hrs)	8
Fuel type Unleaded petrol	Fuel tank capacity (litres)	2.30
	Fuel type	Unleaded petrol





